

# OFFICIALTECH

## 10W40 S2

28/01/2013  
1627

Full synthetic "long-drain" oil, which meets the highest requirements of the leading European manufacturers of heavy trucks. By its selected composition it guarantees the highest level of engine cleanliness. Engine oils according to these specifications are known as UHPD (Ultra High Performance Diesel).

### APPLICATIONS

This oil is used in modern supercharged diesel engines under all service conditions and in all seasons. The high concentration of active additives allows the longest oil drain intervals as prescribed by the manufacturers. Due to the high ash content, this oil is not suitable for gasoline engines and vehicles equipped with a particulate filter.

### FEATURES

Total engine protection: outstanding engine cleanliness and durability.  
Drain interval extension: very long oil drain interval.  
Cold start: very good fluidity at low temperature.

### SPECIFICATION LEVEL

API	CI-4	MACK	EOM PLUS
MB	228.5	MTU	Type 3
MAN	M3277	RENAULT	RLD-2
ACEA	E4-08	RENAULT	RXD
ACEA	E7-08	SCANIA	Approval LDF-2
CUMMINS	CES 20077	VOLVO	VDS-3
CUMMINS	CES 20078	DEUTZ	DQC-III-10

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.873
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	90.7
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	14.0
Viscosity index	ASTM D2270		158
B.N. (HClO <sub>4</sub> method)	ASTM D2896	mg KOH/g	12.5
Pour point	ASTM D6892	°C	-30
CCS viscosity at -25°C	ASTM D5293	mPa.s	6400
Sulfated Ash	ASTM D874	Mass %	1.65
Flash Point COC	ASTM D92	°C	230

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

#### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolfubes.com](http://www.wolfubes.com)

