

RACING 4T 5W50 ESTER

28/01/2013
29183

This is a full synthetic oil for 4-stroke engines, specially used for competition in severe circumstances (circuit, cross, enduro, quads). It offers exceptionally high lubricating power, reduces friction and wear, and extends the performance and life of your motorcycle.

APPLICATIONS

This motor oil was specifically developed for motorcycle sports (road and competition), but can also be used for less heavy duty engines in city traffic and on the road. Qualified for engines with integrated gear boxes without any danger for slipping of the clutch. Resists without any problem high temperatures and reduces deposits.

FEATURES

Engine protection : outstanding engine cleanliness and durability.
Anti-wear and oxidation stability : superior protection.
Temperature stability : very high stability.

SPECIFICATION LEVEL

API	SL	JASO	MA2
JASO	MA		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.854
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	109
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	18.5
Viscosity index	ASTM D2270		190
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	6.6
Pour point	ASTM D6892	°C	-42
CCS viscosity at -30°C	ASTM D5293	mPa.s	3920
Flash Point COC	ASTM D92	°C	235

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfubes.com

