

AROW ISO 32

29/10/2013
4005

A mineral oil, specifically designed to meet the requirements of most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anti-corrosion and anti-foam additives.

APPLICATIONS

This oil is specifically designed to satisfy the requirements of the manufacturers of hydraulic systems where the highest demands are made concerning high pressure, temperatures or speeds. It is recommended for the hydraulic systems of the following types : Vickers, Gerotor, Gresen, HPM, Denison, Cessna, Hydreco and Worthington. It is also suitable for the lubrication of workshop equipment, reducing gears, bearings, compressed air systems and air screw compressors.

FEATURES

Anti-wear and oxidation stability : superior protection.
Anti-foam properties : excellent anti-foam properties.
Temperature stability : adequate viscosity stability.

SPECIFICATION LEVEL

ISO	11158, HM	EATON VICKERS	I-286-S
ISO	6743-4, HM	AFNOR	NF E 48-690
DIN	51524 Part 2	AFNOR	NF E 48-691
AFNOR	NF E 48-603 HM	CINCINATTI	MACHINE P-68 (ISO 32)
DENISON	HF-2	EATON VICKERS	SM-2950-S
CINCINATTI	P68		

TYPICAL CHARACTERISTICS

Test	Method	Unit	{0}
Density at 15°C	ASTM D4052	g/ml	0.872
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	31.4
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	5.4
Viscosity index	ASTM D2270		106
Pour point	ASTM D6892	°C	-30
Flash Point COC	ASTM D92	°C	207

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

