

# AGRIFLOW 4T SAE 30 SJ

28/01/2013  
1503

This is an engine oil specifically designed for the lubrication of modern 4-stroke gasoline engines. The special composition ensures a perfect operation of the equipment and an excellent protection against dirt and deposits.

## APPLICATIONS

It is specifically formulated for the lubrication of the 4-stroke engines of garden and construction machines lawn mowers and auxiliary engines.

## FEATURES

Total engine protection : good engine protection and cleanliness.

## SPECIFICATION LEVEL

API	CD	JASO	MA
API	SJ		

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.888
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	100
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	11,4
Viscosity index	ASTM D2270		99
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	6.0
Pour point	ASTM D6892	°C	-27
Flash Point COC	ASTM D92	°C	235

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolfubes.com](http://www.wolfubes.com)

