# SUPER TRACTOR OIL UNIVERSAL 10W40

28/01/2013 1426

Universal multigrade oil for engines, transmissions, wet brakes and hydraulic systems of agricultural tractors.

#### APPLICATIONS

These oil is recommended for the lubrication of charged and uncharged diesel engines, 4-stroke petrol and LPG engines. This oil is optimized for the lubrication of gearboxes, rear axles, final drives, power take-offs, wet brakes, hydraulic systems of agricultural tractors and off-road equipment.

## FEATURES

Anti-wear and oxidation stability : proven protection of critical parts. Cold start : excellent fluidity at low temperature.

### SPECIFICATION LEVEL

API	CF-4	MAN	271
API	GL-4	ACEA	E2
API	GL-5	ACEA	E3
API	SF/CE	CASE	MAT 3525
FORD	ENS-M2C-121 C	CASE	MAT 3526
FORD	ESN-M2C-134 C/D	MF	M 1127
FORD	ESN-M2C-159B/C	MF	M 1135
FORD	ESN-M2C-86 A/B	MF	M 1139
CATERPILLAR	TO-2	MF	M 1144
MB	227.1	ZF	06B
ALLISON	C4	ZF	07B

# TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.875
Kinematic viscosity at 40°C	ASTM D445	mm²/s	96
Kinematic viscosity at 100°C	ASTM D445	mm²/s	14.1
Viscosity index	ASTM D2270		150
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	10.7
Pour point	ASTM D6892	°C	-36
CCS viscosity at -25°C	ASTM D5293	mPa.s	6700
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.



WOLF OIL CORPORATION NV G. Gilliotstraat 52 – 2620 Hemiksem – Belgium Tel. +32 (0)3 870 00 00 www.wolflubes.com