

OFFICIALTECH

5W30 C1

28/01/2013
65605

Full synthetic, fuel economy "Low SAPS" motor oil for gasoline/LPG and diesel engines of passenger cars with or without turbo, requiring the lowest level of sulphated ash, phosphorus and sulfur.

APPLICATIONS

This oil is specifically designed for the newest generation (Euro 4) gasoline and diesel engines with diesel particulate filters (DPF), which require a low HTHS viscosity oil. It procures a significant improvement in fuel economy.

FEATURES

Aftertreatment protection : full aftertreatment system protection.

Total engine protection : outstanding engine cleanliness and durability.

Fuel economy : lower fuel consumption and CO2 emissions.

SPECIFICATION LEVEL

FORD	M2C-934-B	JASO	DL-1
ACEA	C1-10	MAZDA	SERVICE FILL

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.848
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	55,6
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	10,0
Viscosity index	ASTM D2270		169
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	7,8
Pour point	ASTM D6892	°C	-36
CCS viscosity at -30°C	ASTM D5293	mPa.s	4000
Sulfated Ash	ASTM D874	Mass %	0.5
Flash Point COC	ASTM D92	°C	226

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

