

ECOTECH 0W40 FE

28/01/2013
15106

Full synthetic engine oil of the latest generation, with a large field of application. It offers an excellent fluidity at low temperature, which ensures instant lubrication after starting. This will bring wear to a minimum. Because of its low viscosity, it is fuel-saving.

APPLICATIONS

All 4-stroke gasoline engines, four-valve, turbocharged, and 4-stroke diesel engines with or without turbo. This oil is not suitable for diesel particulate filters.

FEATURES

Total engine protection: performance in keeping the engine clean.

Fuel economy: superior fuel economy and CO₂ reduction.

Cold start: excellent fluidity at low temperature.

SPECIFICATION LEVEL

API	CF	RENAULT	RN 0700
API	SM	RENAULT	RN 0710
MB	229.3	BMW	LOGLIFE-98
VW	502 00	OPEL	GM-LL-B-025
VW	505 00	PORSCHE	PORSCHE
ACEA	A3/B4		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.847
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	78
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	13.7
Viscosity index	ASTM D2270		181
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	9.6
Pour point	ASTM D6892	°C	-39
Sulfated Ash	ASTM D874	Mass %	1.1
Flash Point COC	ASTM D92	°C	216
CCS viscosity at -35°C	ASTM D5293	mPa.s	5700

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfubes.com

