

# OFFICIALTECH

## 75W140 LS GL 5

28/01/2013  
2307

This is a high performance synthetic transmission oil for all differentials, including those equipped with a "limited slip" mechanism. It is characterized by an exceptionally high viscosity stability at different temperatures and a very high fluidity at low temperature.

### APPLICATIONS

This product is used in highly loaded axles and reduction gears of cars, trucks and off-road equipment. It has "limited-slip" characteristics, and is specifically recommended for 4X4 vehicles.

### FEATURES

Frictional properties : very smooth gear shifting, no vibration.

Anti-wear protection : extended transmission life.

Extended oil life : excellent thermal and oxidation stability.

### SPECIFICATION LEVEL

API GL-5 MIL MIL-L-2105 D

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.905
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	170
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	26.5
Viscosity index	ASTM D2270		195
Pour point	ASTM D6892	°C	-51
Flash Point COC	ASTM D92	°C	160

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

#### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolf lubes.com](http://www.wolf lubes.com)

