

OFFICIALTECH

75W80 ZF GL 4

28/01/2013
73010

Semi-synthetic transmission oil for manual synchromesh gear boxes, axles and transfer boxes. This oil has an exceptional synchromesh compatibility, thermal stability and shifting comfort. It is prescribed for industrial vehicles and buses, which are equipped with manual ZF gear boxes.

APPLICATIONS

Especially adapted for ZF Intarder.

FEATURES

Frictional properties : very smooth shift performance.
Anti-wear protection : significantly extended transmission life.
Extended oil life : excellent thermal and oxidation stability.

SPECIFICATION LEVEL

API	GL-4	ZF	TE-ML 02D
MAN	341 Type Z3	EATON	Extended drain
MACK	GO-J	RENAULT	B0032/3 Annex 3
VOLVO	97305		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.880
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	60
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	9,0
Viscosity index	ASTM D2270		125
Pour point	ASTM D6892	°C	-39
Flash Point COC	ASTM D92	°C	235

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

