

EXTENDTECH

85W140 GL 5

28/01/2013
2309

This is an extreme-pressure lubricant for gear boxes, specifically formulated to satisfy the highest service conditions: high speed, shockloads and high torque at low speeds.

APPLICATIONS

Recommended for all hypoid transmissions and also suitable for spiral bevel gears, worm wheels and most transaxles.

FEATURES

Frictional properties : easy gear shifting.
Anti-wear protection : long transmission life.

SPECIFICATION LEVEL

API	GL-5	ZF	TE-ML 16B
MIL	MIL-L-2105 C	ZF	TE-ML 16C
MIL	MIL-L-2105 D	ZF	TE-ML 16D
ZF	TE-ML 05A	ZF	TE-ML 17B
ZF	TE-ML 07A	ZF	TE-ML 19B
ZF	TE-ML 12E		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.908
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	367
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	26.1
Viscosity index	ASTM D2270		95
Pour point	ASTM D6892	°C	-15
Copper corrosion	ASTM D130		1B
Flash Point COC	ASTM D92	°C	215

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfubes.com

