

# AROW ISO 46

29/10/2013  
4006

A mineral oil specifically designed to meet the requirements of most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anti-corrosion and anti-foam additives.

## APPLICATIONS

This oil is specifically designed to satisfy the requirements of the manufacturers of hydraulic systems where the highest demands are made concerning high pressure, temperatures or speeds. It is recommended for the hydraulic systems of the following types : Vickers, Gerotor, Gresen, HPM, Denison, Cessna, Hydreco and Worthington. It is also suitable for the lubrication of workshop equipment, reducing gears, bearings, compressed air systems and air screw compressors.

## FEATURES

Anti-wear and oxidation stability : superior protection.  
Anti-foam properties : excellent anti-foam properties.  
Temperature stability : adequate viscosity stability.

## SPECIFICATION LEVEL

ISO	11158, HM	AFNOR	NF E 48-603 HM
ISO	6743-4, HM	AFNOR	NF E 48-690
DIN	51524 Part 2	AFNOR	NF E 48-691
AFNOR	48-603 HM	CINCINATTI	MACHINE P-70 (ISO 46)
DENISON	HF-2	EATON VICKERS	SM-2950-S
EATON VICKERS	SI-286-S		

## TYPICAL CHARACTERISTICS

Test	Method	Unit	{0}
Density at 15°C	ASTM D4052	g/ml	0.880
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	46.6
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	7
Viscosity index	ASTM D2270		107
Pour point	ASTM D6892	°C	-30
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolf lubes.com](http://www.wolf lubes.com)

