

AGRIFLOW 2T

28/01/2013
1909

This is an outstanding lubricant for 2-stroke engines, based on synthetic components, which combine a high lubricating power with a minimum of deposits and a very high thermal stability. Prediluted for ease of use. Its special formula reduces the formation of exhaust smoke.

APPLICATIONS

It can be added by mixing in the gasoline fuel tank, or by separated lubrication. It was specifically developed for the lubrication of 2-stroke engines of gardening material, chain saws and lawn mowers. For the mixing ratio, always follow the manufacturers' recommendations (average: 3%).

FEATURES

Engine protection : excellent engine performance.
Smoke suppression : smoke reduction.

SPECIFICATION LEVEL

API TC ISO L-EGB
JASO FB

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Color	ASTM D1500		rood
Density at 15°C	ASTM D4052	g/ml	0.880
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	78,8
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	10,5
Viscosity index	ASTM D2270		118
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	1.7
Flash Point COC	ASTM D92	°C	100

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfubes.com

