

EXTENDTECH

ATF DII

28/01/2013
3003

This is an oil with a high viscosity index for automatic transmissions. It is characterized by a high chemical stability, increased anti-wear properties and an excellent resistance against ageing.

APPLICATIONS

It can be used in automatic transmissions, torque convertors, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the General Motors ATF TYPE Dexron II-D requirements.

FEATURES

Anti-wear protection : extended transmission life.
Extended oil life : optimized thermal and oxidation stability.

SPECIFICATION LEVEL

FORD	M2C-138CJ, Mercon	ZF	TE-ML 09
CATERPILLAR	TO-2	ZF	TE-ML 11A
MB	236.7	ZF	TE-ML 14A
ALLISON	C4	ZF	TE-ML 17C
MAN	339 V1/Z1	GM	6137-M DEXRON II-D
ZF	TE-ML 03D	VOITH	55.6335
ZF	TE-ML 04D		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Color	ASTM D1500		rood
Density at 15°C	ASTM D4052	g/ml	0.856
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	37
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	7.4
Viscosity index	ASTM D2270		170
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	3
Pour point	ASTM D6892	°C	-39
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	45000

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfubcs.com

