

CHRONO 2T

28/01/2013
29195

Full synthetic 2-stroke engine oil for high performance, with strong anti-smoke action. To be used in mixed lubrication or with oil injection. Thanks to its special composition, this oil actively reduces friction and wear and is specifically suited for fast performance. It can be used with all sorts of gasoline (with or without lead).

APPLICATIONS

This is a 2-stroke engine oil for high performances and sportive driving. Qualified for all types of 2-stroke engines : motorcycles, scooters and racing replica. Dosage: 2 to 4%, according to the manufacturer's recommendations.

FEATURES

Engine protection : outstanding engine cleanliness and durability.

Smoke suppression : excellent smoke reduction.

Corrosion protection : adequate corrosion protection.

SPECIFICATION LEVEL

API	TC	JASO	FD
JASO	FC	ISO	L-EGD

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.875
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	72.2
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	10.8
Viscosity index	ASTM D2270		138
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	1.2
Flash Point COC	ASTM D92	°C	100

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

