

# VITALTECH

## MULTI VEHICLE ATF

28/01/2013  
3010

Full synthetic fluid for automatic transmissions with a very high viscosity index, excellent oxidation stability, excellent friction and anti-wear properties, meeting the requirements of most American, Japanese and European manufacturers.

### APPLICATIONS

It can be used in automatic transmissions and torque convertors for most passenger cars, off-road vehicles and SUVs.

### FEATURES

Frictional properties : very smooth gear shifting, no vibration.  
Anti-wear protection : significantly extended transmission life.  
Extended oil life : excellent thermal and oxidation stability.

### SPECIFICATION LEVEL

FORD	MERCON	ZF	TE-ML 17C
FORD	MERCON V	GM	DEXRON II-D
MB	236.11	GM	DEXRON III-G
MB	236.3	GM	DEXRON III-H
MB	236.5	VOITH	G 607
MB	236.7	CHRYSLER	ATF +3 AND +4
MB	236.9	MITSUBISHI	DIAMOND SP II
MB	236.10	MITSUBISHI	DIAMOND SP III
ALLISON	C4	NISSAN MATIC	D, J, K
ZF	TE-ML 03D	TOYOTA	TYPE T
ZF	TE-ML 04D	TOYOTA	TYPE T-III
ZF	TE-ML 14A	TOYOTA	TYPE-IV
ZF	TE-ML 14B	AUDI	G 55 025 A2
ZF	TE-ML 16L		

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Color	ASTM D1500		red
Density at 15°C	ASTM D4052	g/ml	0.861
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	35.6
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	8.1
Viscosity index	ASTM D2270		212
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	12000
Copper corrosion	ASTM D130		1B
Flash Point COC	ASTM D92	°C	178

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

#### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolfubes.com](http://www.wolfubes.com)

