

OUTBOARD 2T TC-W3

28/01/2013
1912

This is an oil for water-cooled 2-stroke outboard engines, meeting the NMMA-specification TC-W3. Its ashless composition prevents the formation of deposit, pre-ignition and spark plug fouling. High protection against rust and corrosion.

APPLICATIONS

All water-cooled 2-stroke gasoline engines with high power, such as outboard motors, jet skis and personal watercraft. Dilution according to the manufacturer's instructions.

FEATURES

Engine protection : outstanding engine cleanliness and durability.
Corrosion protection : adequate corrosion protection.

SPECIFICATION LEVEL

NMMA TC-W3 OMC 40/70

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Color	ASTM D1500		DarkBorG
Density at 15°C	ASTM D4052	g/ml	0.875
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	42,5
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	7,0
Viscosity index	ASTM D2270		124
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	4.0
CCS viscosity at -25°C	ASTM D5293	mPa.s	5740
Flash Point COC	ASTM D92	°C	105

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfubes.com

