

FUN 4T 15W40

28/01/2013
29188

High quality multigrade engine oil for daily use in small 4-stroke engines. Its formulation is adapted for integrated gear boxes and is very suitable for smaller 4-stroke engines for normal use. Also applicable for engines with somewhat older technology.

APPLICATIONS

It is intended for daily use and for city traffic of smaller engines, like scooters, motorbikes and mopeds.

FEATURES

Engine protection : excellent engine performance.
Anti-wear and oxidation stability : adequate protection of systems.

SPECIFICATION LEVEL

API	SL	JASO	MA2
JASO	MA		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.880
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	103
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	13.9
Viscosity index	ASTM D2270		137
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	7
Pour point	ASTM D6892	°C	-33
CCS viscosity at -20°C	ASTM D5293	mPa.s	6500
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfiubes.com

