

CHRONO 4T 10W40

28/01/2013
29185

This is a synthetic-based oil for 4-stroke engines for normal and intensive use. Based on an enforced formula with extreme pressure additives for gear boxes. Its special formulation avoids slipping of the wet clutches and has excellent dispersant and detergent action. It offers optimum protection and longer lifetime of the engine.

APPLICATIONS

This motoroil is qualified for normal and fast driving in city traffic and on the highway and can be used for all types of motorcycles : road, cross/trial, enduro, quads.

FEATURES

Engine protection : outstanding engine cleanliness and durability.
Anti-wear and oxidation stability : superior protection.
Temperature stability : superior viscosity stability.

SPECIFICATION LEVEL

API	SL	JASO	MA2
JASO	MA		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.876
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	91
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	14.1
Viscosity index	ASTM D2270		160
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	6.6
Pour point	ASTM D6892	°C	-39
CCS viscosity at -25°C	ASTM D5293	mPa.s	5600
Flash Point COC	ASTM D92	°C	224

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfubes.com

