

TRANSLUBE 10W30 80W

28/01/2013
2001

Specific lubricant for gearboxes in motorcycles with 2-stroke engine with integrated clutch. Its special composition assures an easy gear shifting and controls the slipping characteristics of the clutch for smooth driving conditions.

APPLICATIONS

This oil is qualified for all gearboxes with clutch in an oil bath. Excellent detergent properties for the clutch lining together with a very resisting oilfilm and good extreme pressure properties.

FEATURES

Extreme pressure properties : good EP properties.
Anti-wear and oxidation stability : adequate protection of systems.

SPECIFICATION LEVEL

API GL-3

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.877
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	65
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	10.1
Viscosity index	ASTM D2270		141
Pour point	ASTM D6892	°C	-30
Flash Point COC	ASTM D92	°C	215

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfubcs.com

